

**Indoor/Outdoor Paging Speaker****C-C-PHSI-7S**

Indoor/Outdoor Paging speaker for public address announcement applications. It is finished with powder coating, and stainless steel hardware & bracket to ensure weatherproof capability.

Rated Input	15 W
Line Voltage	70 V line or 25 V line
Rated Impedance	70 V line: 330 Ω (15 W), 650 Ω (7.5 W), 1.3 K Ω (3.8 W) 25 V line: 42 Ω (15 W), 83 Ω (7.5 W), 330 Ω (1.9 W), 650 Ω (1 W), 1.3K Ω (0.5 W)
Sound Pressure Level	112 dB (1 W, 1 m at 500 Hz to 2.5 kHz peak level)
Frequency Response	280 Hz – 12.5 kHz
Sensitivity when used as a Microphone (0 dB=1 mW/10 dynes/cm ²)	-22 dB at 1 kHz
Dust/Water Protection	IP65
Polarity	Hot: Black, Com: White
Operating Temperature	-20 °C to 55 °C (must be free from dew condensation)
Finish	Horn flare: Aluminum, off-white, powder coating Reflector horn and rear cover: ABS resin, off-white Bracket, screws and bolts: Stainless steel Speaker cable: Polyvinyl chloride insulated cabtyre cable (6 mm in diameter, 600 mm in length)
Dimensions	222 (W) x 179 (H) x 234 (D) mm
Weight	103 kg