

Bright visual notification of telephone, safety, and security events. Effective and selectable flash patterns radiate light 360 x 180 degrees for visibility in all directions. Alerts employees in noisy locations and eliminates noise in quiet environments.

- PoE Endpoint
- SIP, multicast, or dry contact activated
- Selectable flash pattern, rate and intensity
- Optional amber, blue or red covers
- Wall or ceiling mountable
- Weather resistant

| MODEL | C-C-CT |
|-----------------|--|
| Power Input | 48 V PoE Class 0 (Maximum 12.95 W - Idle nominal 1 W) |
| Size | 4.8" W x 4.8" H x 3.0" D (12.2cm W x 12.2cm H x 7.6cm D) |
| Optical | 8 LEDs, 643 lumens, 198 Cd |
| Strobe Triggers | SIP extension ring, Subscribe/Notify, multicast, dry contact input |
| Relay Output | Max 30 V 50 mA |
| Relay Input | Max 1 kOhm |
| Flash Patterns | 16 Selectable patterns |
| Programming | Web interface |
| Provisioning | TFTP, FTP, or HTTP |
| NAT | STUN, CRLF Keep Alive |
| Environmental | -4 to +122 deg F (-20 to +50° C); 10-95% RH noncondensing. Dry indoor location only unless wiring cavity protected from water ingress using supplied gaskets or other protective measures. |
| Compliance | EN60950:2001, IEEE 802.3-2008, RFC3261, RoHS, CE, FCC, CSA (USA & Canada) |



Flexible.
Wall or Ceiling Mounted