



# 70 Volt 2X2 Ceiling Speaker

## CC2X2LI7S



### Speaker

<b>Average Sensitivity:</b>	92dB SPL, 1W/1M
<b>Loudspeaker Power Rating:</b>	12W RMS, EIA 426A Standard
<b>Maximum Output:</b>	4W @ 25/70V
<b>Calculated Output:</b>	98dB SPL, 4W/1M
<b>Magnet Type and Weight:</b>	BeFe Ceramic, 5 oz. Nominal
<b>Frequency Response:</b>	65Hz - 17kHz, EIA 426A Standard
<b>Nominal Coverage Angle:</b>	100° Included Angle, -6dB/2kHz, Half Space
<b>Audio Connection:</b>	7 ½", Color-coded, Pre-tinned Leads

### Application

<b>Intended Use:</b>	Lay-in ceiling tile replacement
<b>Program Material:</b>	Signal tones, voice and music
<b>Installation:</b>	Mounted parallel to floor plane in a 24" wide ceiling grid

### Component

<b>Dimensions:</b>	23 13/16" x 23 13/16" x 3 1/2"
<b>Weight:</b>	6.37 lbs.
<b>Loudspeaker Specs:</b>	8" O.D. loudspeaker, 5 oz. magnet
<b>Finish:</b>	White powder coat
<b>Transformer:</b>	4W, 25/70V, rotary select with 5 taps (0.25W, 0.50W, 1W, 2W, 4W)

### Certifications

<b>UL Listed 1480</b> <b>UL Listed 2043</b>	When installed with supplied installation instructions and requirements of NEC/AHJ. (UEAY, UEAY7- Canada) Suitable for use in air-handling spaces
------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------