



8 Ohm 2X2 Ceiling Speaker

CL2X2LI8B



Speaker

| | |
|----------------------------------|--|
| Average Sensitivity: | 95dB SPL, 1W/1M |
| Loudspeaker Power Rating: | 20W RMS, EIA 426A Standard |
| Maximum Output: | 20W @ 8 Ohms |
| Calculated Output: | 98dB SPL, 4W/1M |
| Magnet Type and Weight: | BeFe Ceramic, 10 oz. Nominal |
| Frequency Response: | 60Hz - 17kHz, EIA 426A Standard |
| Nominal Coverage Angle: | 100° Included Angle, -6dB/2kHz, Half Space |
| Audio Connection: | 7 ½", Color-coded, Pre-tinned Leads |

Application

| | |
|--------------------------|--|
| Intended Use: | Lay-in ceiling tile replacement |
| Program Material: | Signal tones, voice and music |
| Installation: | Mounted parallel to floor plane in a 24" wide ceiling grid |

Component

| | |
|---------------------------|--|
| Dimensions: | 23 13/16" x 23 13/16" x 3 1/2" |
| Weight: | 6.05 lbs. |
| Loudspeaker Specs: | 8" O.D. loudspeaker, 10 oz. magnet |
| Finish: | White powder coat |
| Grille: | Standard perforated steel with four (4) seismic tie-off points |

Certifications

| | |
|--|--|
| UL Listed 1480 UL Listed 2043 | When installed with supplied installation instructions and requirements of NEC/AHJ. (UEAY, UEAY7- Canada) Suitable for use in air-handling spaces |
|--|--|