



G2 SIP Video Intercom Console Phone

C-C-VICP



Features Overview

- 20 SIP Lines
- 7" Capacitive Color Touch-screen
- HD Audio on Speakerphone and Handset
- V1 Version Supports Bluetooth 2.1
- V2 Version Supports Bluetooth 4.2
- V1 Version Supports 3-way Conference
- V2 Version Supports 6-way Conference
- Dual Gigabit Ports, Integrated PoE
- Up to 127 DSS Key Entries Available at the Display
- Wi-Fi Connectivity (via Wi-Fi Dongle)
- Be able to Receive Video Call (V1 Version, supports H.264, V2 Version Supports H.264 & 1080p)
- Stand with 2 Adjustable Angles of 40 & 50 degrees
- Support EHS Headset

Phone Features

- Local Phonebook (2000 entries)
- Remote Phonebook (XML/LDAP, 2000 entries)
- Call Logs (In/Out/missed, 1000 entries)
- Network Time Synchronization
- Programmable DSS/Soft Keys
- Voice Message Waiting Indication
- uaCSTA

Audio/Video

- HD Voice (Microphone/Speaker) ~7KHz Frequency Response
- Wideband Codec: G.722, Opus
- Narrowband Codec: G.711a/u, G.723.1, G.726-32K, G.729A/B, iLBC
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) Background Noise Estimation (BNE) / Noise Reduction (NR) Automatic Gain Control (AGC)
- Video Codec: H/264
- Video Call Resolution: QCIF/CIF / VGA/1080p



Call Features

- Call Out/Answer/Reject
- Intercom and Speed Dial
- Caller ID Display
- Call Forwarding/Transferring/Parking
- Do Not Disturb
- Auto-Answering
- Hot Line

Networking

- Physical: 10/100/1000 Mbps Ethernet
- IP Mode: IPv4/IPv6/IPv4&IPv6
- IP Configuration: Static/DHCP/PPPoE
- Network Access Control: 802.1x
- VPN: L2tp/OpenVPN

Protocols

- SIP2.0 Over UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN
- DHCP
- IPv6
- HTTP/HTTPS
- TR-069
- LLDP
- PPPoE
- 802.1x
- L2TP
- OpenVPN
- SNTP
- FTP/TFTP

Physical Specifications

- Main LCD x1: 7.0 Inch (1024x600) Capacitive Touch Screen
- Keypad - 26 Keys
- HD Handset (RJ9) x1
- Standard RJ9 Handset Wire x1
- 1.5M Cat5 Ethernet Cable x1
- Back Rack x1
- RJ9 Port x2: Handset x1, Headset x1
- RJ 45 Port x2: Network x1, PC x1 (Bridged Network)
- USB 2.0 Port x1
- DC Power Input: 5V/2A
 - Power Consumption (PoE): 2.6~9W
 - Power Consumption (Adapter): 2.4~8W
- Working Temp: 0~45°C
- Working Humidity: 10~95%
- Installation: Desktop Stand



888.859.1274



info@galaxynext.us



www.galaxynext.us