



4 Channel Video Decoder VWD4C



General

Dimensions:	17.4" x 13.4" x 1.75"
Weight:	7.25lbs
Working Temperature:	14°F ~ 131°F
Working Humidity:	10% ~ 90%(No-condensing)
Power Supply:	100V ~ 240V AC; 50Hz/60Hz
Consumption:	20W

External Interface

Audio Input:	2-ch (Reservation)
Audio Output:	1-ch (3.5mm)
Alarm Input:	6 (Reservation)
Alarm Output:	3 (Reservation)
USB Interface:	1x USB 3.0
Serial Interface:	1x RS-232, 1x RS485
Network Interface:	1x RJ-45 , 10M/100M/1000M adaptive Ethernet Interfaces

Video Decoding

Video Stream Format:	H.265, H.264, MPEG4, MPEG2, MJPEG
Decoding Capability:	4x3840x2160@30, 16x1080P@30, 36x720P@30, 64xD1
Display Split:	1/2/3/4/6/7/9/16



4 Channel Video Decoder VWD4C



Video Output

Output Channel:

4

HDMI Output:

3840x2160(4K)@60HZ, 3840x2160(4K)@30HZ,
1920x1080(1080P)@60HZ, 1600x1200(UXGA)@60HZ,
1440x900(WXGA+)@60HZ, 1280x1024(SXGA)@60HZ,
1280x720(720P)@60HZ, 1024x768(XGA)@60HZ

Video Input

Input Channel:

2x HDMI

HDMI Input:

1920x1080(1080P)@60HZ, 1920x1080(1080P)@50HZ,
1600x1200(UXGA)@60HZ, 1440x900(WXGA)@60HZ,
1280x1024(SXGA)@60HZ, 1280x720(720P)@60HZ,
1280x720(720P)@50HZ, 1024x768(XGA)@60HZ