



Base Station and Amplifier

Amplifier Type:	Class D Amplifier
Integrated Microphone Receiver:	Connect any combination of our six G2 LINK teacher or student microphones
Compatible Microphones:	G2 LINK microphones
Network:	10/100Mbps Wi-Fi (When using a G2 LINK Wi-Fi Dongle)
Speaker Configurations:	2, 4, 6 or 8 (4 speakers typical)
Continuous Power:	60 Watts (30 Watts (RMS) per channel x 2 channels @ 4 ohms) Secondary Amp powered by PoE (10 Watts per channel)
Signal to Noise;	>65 dB
Tone Control:	Yes
Frequency:	DECT RF (Does not interfere with Bluetooth or Wi-Fi)

Enviromental

Storage Temperature:	-40 to 158°F
Storage Humidity:	10–90% non-condensing

Dimensions and Weight

Overall Dimensions:	9.25" x 3.75" x 1.25"
Net Weight:	12oz
Enclosure:	PC/ABS plastic UL compliant



Controls and Integration

User Control:	Volume control (inputs and output levels) plus mute Preset equalizer and multiband settings Network settings and Bluetooth pairing Streaming audio control Firmware updatable
User Control Level:	Multiple User Level (User and IT)
Presentation Control:	When connected from the AMP via USB-C to the computer, use the Teacher Microphone to advance the presentation either Page Up or Down.