



SIP IP Speaker, LCD and Microphone CIPSPKMDC



Speaker	
Speaker Size:	4.5" inch
Average Sensitivity:	91dB/1m/1W
Max Sound Pressure:	101dB
Amplifier:	Single Channel Class-D Topology
Rated Power:	8Ω 10W
Frequency Response:	70Hz – 20KHz
Audio	
Audio Codecs:	G.722, G.711 A-law, G.711 U-law, Opus
Network	
Ethernet:	IEEE 802.3 10/100Base-T
PoE:	IEEE 802.3 AT Compliant
Supported Protocols:	SIP (RFC3261), HTTP, TCP/IP, SSL, DNS, SNTP, NTP, RTSP, RTP, RTCP, TCP, UDP, MQTT, ICMP, DHCP, ARP, SSH
IP Addressing:	DHCP/Static
Mechanical Properties	
Memory:	128HM RAM, 265 Flash
AC Power Input:	PoE+ and External 24VDC
Environmental Properties	
Installation Environment:	Indoor
Operating Temp and Humidity:	-4°F - 122°F / 10% - 95% RH Non-Condensing
Physical Specifications	
Casing Material:	Cold Rolled Steel Finish in Textured White Epoxy
Installation Methods:	Surface Mounted
Color:	White
Dimensions (Surface):	11.81" x 11.81" x 3.62"
Weight:	7.72lbs
Certifications	
Certifications:	EN55032:2015, EN55035:2017, EN61000-3-2:2014, EN61000-3-3:2013, EN62368-1:2014+A11:2017, FCC Part 15B Class A



Scrolling Text Alert

LCD screen supports customizable scrolling alerts, with customizable background colors and text content for display. This flexibility makes it suitable for various industries.



Clock

The LCD screen displays time and date, eliminating the need for a separate clock system, perfect to use in scenarios like classrooms, libraries, offices. Viewable at 65 ft.