

WorkForce 5 is an Office Phone for your employees. It is perfect for amplifying your efficiency and monitoring your coworkers' availability thanks to the integrated Collaboration feature.

HIGHLIGHTS

- | | |
|---|--|
| <ul style="list-style-type: none"> • 2.8" color display 320*240 • USB2.0 Port x1: Standard A • USB Headset-compatible • USB Bluetooth dongle connectivity • Opus compatibility • WiFi dongle-ready • Presence monitoring | <ul style="list-style-type: none"> • Caller image • Dual Gigabit Port 10/100/1000 • PoE IEEE 802.3af • Integrated PoE • Audio HD wideband • Max 21 BLF keys (3 pages) • Visual/ audio BLF • 802.3az Green Ethernet |
|---|--|



TECH SPECIFICATIONS

Phone & PBX

- | | |
|---|---|
| <ul style="list-style-type: none"> • Presence • New Voicemail / Missed call / New call notification • Online access to PBX phonebooks • Sync of call history and missed call notifications • PBX ringtones | <ul style="list-style-type: none"> • Intercom, paging, speed dial, hold, 3-way conference call; redial, mute, call transfer, call pickup, group call pickup, music on hold • Multi-language support |
|---|---|

Audio

- | | |
|--|--|
| <ul style="list-style-type: none"> • HD audio with wideband codec G.722, Opus • Narrowband codec G.711a, G.729 | <ul style="list-style-type: none"> • HD voice speaker • Full-duplex Echo canceller |
|--|--|

Security & Networking

- | | |
|--|--|
| <ul style="list-style-type: none"> • SIP2.0 over TLS; QoS; VLAN; RTP/RTCP | <ul style="list-style-type: none"> • SRTP |
|--|--|

Supported Headsets

- | | |
|--|---|
| <ul style="list-style-type: none"> • RJ-9 connector, USB connector • MonoLED, DuoLED | <ul style="list-style-type: none"> • 3rd party headsets: https://wildix.atlassian.net/wiki/x/DhTOAQ |
|--|---|

Physical

- | | |
|---|--|
| <ul style="list-style-type: none"> • 21 BLF keys (3 pages) • 2.8" 320x240 color display • 1 x RJ9 headset port; 1 x RJ9 handset port; USB2.0 Port x1: Standard A for a USB headset and WorkForce WiFi Dongle (available as a HWaaS item) • 802.3az Green Ethernet • PoE IEEE 802.3af | <ul style="list-style-type: none"> • Optional Power Adapter (Product code: PS-5V2A): Input AC 100-240 V; Output DC 5 V/ 2 A; Max power consumption: 6.3W • 2 x RJ45 10/100/1000 Mb Ethernet ports • Giftbox size: 307*258*71 mm • Operating t°: 32~113 °F, 0~45°C; Storage t°: -22~140 °F, -30~60°C; Humidity: 10~95% Non-condensing |
|---|--|